

SAFETY DATA SHEET

SECTION 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name: SURESEAL

Other Names:

Recommended Use: Solventborne sealer for masonry, plaster and gib

Company Name: Resene Paints Limited New Zealand

Address: 32-50 Vogel Street, Naenae, Wellington, NEW ZEALAND
P O Box 38242, Wellington Mail Centre

Phone: (04) 577 0500 Fax: (04) 577 0600

Resene Paints Limited Australia

Address 7 Production Avenue, Molendinar, Queensland 4214
P O Box 785, Ashmore City, Queensland 4214
AUSTRALIA

Phone 1800 738 383

Emergency Telephone:

New Zealand 0800 737 363 Available Monday - Friday 8.00am - 4.30pm

New Zealand Poisons Centre: 0800 764 766

Australia 1800 738 383

Australian Poisons Centre: 131 126

SECTION 2. HAZARDS IDENTIFICATION

Hazard Classification HAZARDOUS according to NZ HSNO Regulations
Regulated under NZS5433 for land transportation

Risk Phrases Not assigned

Safety Phrases Not assigned

Substance Classification 3.1C 6.3B 6.5B 6.7B 9.1B

Hazard Statements Flammable liquid and vapour
Causes mild skin irritation
May cause an allergic skin reaction
Suspected of causing cancer
Toxic to aquatic life with long lasting effects

SECTION 3. COMPOSITION / INFORMATION ON INGREDIENTS

Ingredients	%	CAS No	TWA	
White Spirit	30-60	8052-41-3	525 mg/m ³	NZ OSH (WES) 2002
CI Pigment Yellow 53	<1	8007-18-9	Not Known	
Methyl Ethyl Ketoxime	<1	96-29-7	36 mg/m ³	OSHA CEL
Alkyd Resin	10-30	Not known	None Establish	
Proprietary ingredients		various	None Establish	

SECTION 4. FIRST AID MEASURES

Eyes Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do so. Continue rinsing. If eye irritation persists get medical attention/advice.

Swallowed: Call a POISON CENTRE (NZ 0800 764766) or Australia (131 126) or doctor/physician if you feel unwell.

Skin IF ON SKIN: Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. IF skin irritation occurs: Get medical advice/attention.

Inhaled IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing

Aggravated medical conditions caused by exposure

Chronic Health Effects Not Identified

Advice to Doctor Treat symptomatically

SECTION 5. FIRE FIGHTING MEASURES

Extinguisher Foam, Carbon Dioxide, Dry Chemical

Hazards from combustion products

Special protective precautions and equipment for firefighters

Fire/Explosion Hazard

Auto Ignition Temperature

Lower Explosion Limit

Upper Explosion Limit

Hazchem Code

Flash Point

Not calculated

Not calculated

Not calculated

3[Y]

31°C

SECTION 6. ACCIDENTAL RELEASE MEASURES

Emergency Procedures

Keep spectators away and avoid breathing dust or vapours

Methods and materials for containment and clean up

Minor Spills Use absorbent clean up materials, such as fire retardant treated sawdust or diatomaceous earth.

Keep spills (and as much as possible cleaning runoffs) out of municipal sewers and waterways.

Wear protective clothing and breathing apparatus.

Sweep up.

Place in separate container for disposal or recovery.

Clean up spills immediately.

Major Spills Dike and contain spill with inert materials (eg. Sand).

Keep spills (and as much as possible cleaning runoffs) out of municipal sewers and open bodies of water.

Restrict access to area. No smoking or naked lights.

Clear area of personnel and move upwind.

Alert Fire Brigade and tell them location and nature of hazard.

Consider evacuation (or protect in place).

Stop leak if safe to do so.

Collect recoverable product into labelled containers for recycling.

SECTION 7. HANDLING AND STORAGE

Precautions for safe handling Avoid damaging containers. Keep lids on containers when not in use

Conditions for safe storage including any incompatibilities Not Identified

Storage Temperatures Min 1°C

Max 40°C

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

National exposure standards for mixture No exposure standards has been established for this product

Component

Breathing Zone ppm

Breathing Zone mg/m³

Personal Protection

Eye: Safety eyewear with splash guards or side shields to prevent eye contact is recommended when using any paint.

Hands/Feet Protective clothing. Gloves of neoprene or nitrile rubber - Industrial weight lined gauntlet recommended.

Other Overalls, impervious clothing, barrier cream, eyewash unit, skin cleansing cream.
Practice good caution and personal cleanliness to avoid skin contact. Avoid breathing vapours of heated materials. Wash hands thoroughly before handling food.

Respirator None required

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance coloured viscous liquid

Odour	pH	Vapour Pressure	Vapour Density	Boiling Point	Melt Freeze	Solubility	Volatile by Weight
Hydrocarbon	n/a	1.33 kPa	4.0	126°C	-77°C	Immiscible	45

SECTION 10. STABILITY AND ACTIVITY

Chemical Stability Product is considered stable under normal storage and handling conditions.

Conditions to Avoid Freezing, excessive heat and changes in temperature

Incompatible Materials

Hazardous decomposition product Oxides of carbon and nitrogen

Hazardous reactions Hazardous polymerisation will not occur.

SECTION 11. TOXICOLOGICAL INFORMATION

No data available for this product

Component

Oral:LD50 mg/k

Dermal:LD50 mg/k

Inhale:LC50 pp

SECTION 12. HAZARDS IDENTIFICATION

Do not allow the product to enter the environment

No data available for this product

Component

Fish:LC50 mg/Lt

BCF:<100 Kow

SECTION 13. DISPOSAL CONSIDERATIONS

Special precautions for landfill or incineration

Consult manufacturer for recycling options and recycle where possible

Decontaminate empty containers. Observe all label safeguards until containers are cleaned and destroyed

SECTION 14. TRANSPORT INFORMATION

Transport only in accordance with the following regulations

UN Number 1263

Proper Shipping Name Paint related product

Subsidiary Risk

Poison Schedule

Packing Group: III

Class 3

HAZCHEM Code 3[Y]

Special precautions for user**SECTION 15. REGULATORY INFORMATION**

Group Standard HSR002669 Surface Coatings & Colourants - Flammable, Toxic[6.7]

Approved Handler Not required

SECTION 16. OTHER INFORMATION

Date of Preparation 31/10/2011

Literature references MSDS's for individual raw material

Abbreviations:

NOHSC National Occupational Health and Safety Commission

TWA Time weighted average

STEL Short term exposure limit

CAS Number Chemical Abstract Service registry number

TLV Threshold limit value

Marine Pollutant Marine Pollutant ☐**Safety data sheets are updated frequently. Please ensure that you have a current copy**

The information contained herein is based on data considered accurate and reliable to the best of our knowledge and belief as of the date compiled. However no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use hereof. Resene Paints (New Zealand) Limited assumes no responsibility for personal injury or property damage to vendors, users or third parties caused by the material. Such users or vendors assume all risks associated with the use of the material. It is the users responsibility to satisfy themselves as to the suitability and completeness of the information for their own particular use. The users must determine whether the use of the information and data is in accordance with local laws and regulations.