

IBS PRIMActu



CARE AND MAINTENANCE GUIDE AUGUST 2021

PRIMActu is a tiling underlay manufactured from cellulose fibre cement. Each panel has a smooth, sanded face which is sealed and ready for tiling.

The panels are manufactured in a high-pressure chamber (called an autoclave) from high-grade cellulose pulp fibre, finely ground sand, Portland cement and water.

This process makes PRIMActu strong, durable and non-combustible. The panels are also moisture resistant and can help with soundproofing.

To save on construction time, the panels are supplied with a pre-marked nailing pattern.

We recommend using PRIMActu as:

- an internal dry floor underlay for use in wet areas
- a flat, even floor surface that can be covered with ceramic, mosaic, natural stone tiles or carpet.



Maintaining PRIMActu

Under normal conditions PRIMActu will need no maintenance. Maintaining the protective finished layer will ensure that the floor retains the desired look and feel.

If water damage does occur to an area where PRIMActu has been used, first remove the protective layer then make sure the area is allowed to dry thoroughly before you replace any protection. The moisture content is to be approximately between 12% and 14% before resealing.

Maintaining the protective layer will depend on the manufacturer's requirements of the specific finish. Typically it will include:

- Regularly washing and/or wiping clean protective surfaces to remove mould, scale and/or soap deposits
- Checking the sealant joints around fixtures
- Checking the grout joints between ceramic tiles
- Removing any loose or defective grout and replace in part or all (as required)
- Checking that the paint or plaster system is maintained.

Scan the QR code to view all
IBS PRIMActu documents.



NZBN 9429000097253

PRIMActu Product Details

L x W x Thickness (mm)	Weight (kg)	IBS Product Code	GTIN
1800 x 900 x 6	13.5	PRIMACTU06189	09421028760379
1800 x 1200 x 6	18	PRIMACTU061812	09421028760386