

TRADE-SEAL is a one piece self adhesive collar for sealing around pipe and conduit.

Sizes available:

8-12 mm

15-22 mm

25-32 mm

42-55 mm

50-70 mm

75-90 mm

100-110 mm

125-135 mm

150-165 mm

200-220 mm



BRANZ Appraised
Appraisal No.719 [2011]



Installation Instructions:

- Step 1. Select the appropriate sized TRADE-SEAL from within the range to suit pipe or conduit diameter. TRADE-SEAL's should never be forced over pipes or conduit.
- Step 2. Ensure the surface to receive the TRADE-SEAL is clean and dry.
- Step 3. Slide the TRADE-SEAL over the pipe or conduit until the EPDM boot achieves a snug fit. Some TRADE-SEAL's may require trimming to ensure there isn't excessive tension on the boot. If trimming is required slide the TRADE-SEAL over the pipe or conduit until it becomes tight, mark this point of the boot. Remove the boot and trim the excess rubber then re-check for a snug fit.
- Step 4. Slide the TRADE-SEAL into place over the pipe/conduit & push firmly against the building underlay or RAB. Remove the backing release film & press firmly onto the underlay/RAB.

Note: Make sure the TRADE-SEAL is placed in a diamond shape to ensure effective water run-off.
- Step 5. Smooth the TRADE-SEAL onto the substrate to ensure adequate adhesion.
- Step 6. Push TRADE-SEAL collar back on to penetration to fit cavity width.

Note: Never force TRADE-SEAL's over pipes or conduit.

