**CEILING VELVET** Version Number: 1

# SAFETY DATA SHEET

#### IDENTIFICATION OF THE MATERIAL AND SUPPLIER SECTION 1.

**CEILING VELVET Product Name:** 

Other Names:

**Recommended Use:** 

**Company Name:** Resene Paints Limited New Zealand Address: 32-50 Vogel Street, Naenae, Wellington, NEW ZEALAND

P O Box 38242, Wellington Mail Centre

Phone: (04) 577 0500 Fax: (04) 577 0600

> 7 Production Avenue, Molendinar, Queensland 4214 Resene Paints Limited Australia **Address**

P O Box 785, Ashmore City, Queensland 4214

**AUSTRALIA** 

**Phone** 1800 738 38

**Emergency Telephone:** 

0800 737 363 Available Monday - Friday 8.00am - 4.30pm **New Zealand** 

New Zealand Poisons Centre: 0800 764 766

**Australia** 1800 738 383

**Australian Poisons Centre: 131 126** 

SECTION 2. HAZARDS IDENTIFICATION

Hazard Classificaton HAZARDOUS according to NZ HSNO Regulations

Regulated under NZS5433 for land transportation

**Risk Phrases** Not assigned **Safety Phrases** Not assigned

Substance Classification 3.1C 6.3A 6.4A 6.5B 6.8B 6.9B

**Hazard Statements** Flammable liquid and vapour

> Causes mild skin irritation Causes eye irritation

May cause an allergic skin reaction

Suspected of damaging fertility or the unborn child.

Suspected of damaging organs through prolonged or repeated

exposure

#### SECTION 3. COMPOSITION / INFORMATION ON INGREDIENT

| Ingredients               | %     | CAS No     | TWA            |                   |
|---------------------------|-------|------------|----------------|-------------------|
| Hydrocarbons Liquid       | 10-30 | 64742-47-8 | Not Known      |                   |
| Magnesium Silicate (Talc) | 1-10  | 14807-96-6 | 2 mg/m³        | NZ OSH (WES) 2002 |
| Hexylene glycol           | 1-10  | 107-41-5   | Not known      |                   |
| Proprietary ingredients   | 30-60 | various    | None Establish |                   |

#### SECTION 4. FIRST AID MEASURES

Eyes Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do so.

Continue rinsing. If eye irritation persists get medical attention/advice.

Call a POISON CENTRE (NZ 0800 764766) or Australia (131 126) or doctor/physician if you feel Swallowed:

unwell.

Remove/take off all contaminated clothing and wash before re-use. Wash skin with water/shower and Skin

plenty of soap. If skin irritation occurs get medical advice/attention.

IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing Inhaled

If experiencing breathing difficulties urgently seek medical attention.

Aggravated medical conditions caused by exposure

Chronic Health Effects Not Identified Advice to Doctor Treat Symptomatically

#### FIRE FIGHTING MEASURES SECTION 5.

**CEILING VELVET** Resene Paints Limited Page 1 of 4

Extinguisher Foam, Carbon Dioxide, Dry Chemical

Hazards from combustion products

Special protective precautions and equipment for firefighters

Fire/Explosion Hazard Auto Ingnition Temperature Lower Explosion Limit Upper Explosion Limit

260℃ 5.7% 0.8% **Hazchem Code Flash Point** 

40℃ 3[Y]

#### ACCIDENTAL RELEASE MEASURES SECTION 6.

## **Emergency Procedures**

Keep spectators away and avoid breathing dust or vapours

## Methods and materials for containment and clean up

Minor Spills Use absorbent clean up materials, such as fire retardant treated sawdust or diatomaceous earth.

Keep spills (and as much as possible cleaning runoffs) out of municipal sewers and waterways.

Wear protective clothing and breathing apparatus.

Sweep up.

Place in separate container for disposal or recovery.

Clean up spills immediately.

Major Spills Dike and contain spill with inert materials (eg. Sand).

Keep spills (and as much as possible cleaning runoffs) out of municipal sewers and open bodies of water.

Restrict access to area. No smoking or naked lights.

Clear area of personnel and move upwind.

Alert Fire Brigade and tell them location and nature of hazard.

Consider evacuation (or protect in place).

Stop leak if safe to do so.

Collect recoverable product into labelled containers for recycling.

#### SECTION 7. HANDLING AND STORAGE

Precautions for safe handling Avoid damaging containers. Keep lids on containers when not in use Conditions for safe storage including any incompatibilities

**Storage Temperatures** Max 40°C Min 0ºC

Incompatibilities

#### EXPOSURE CONTROLS/PERSONAL PROTECTION SECTION 8.

**National exposure** standards for mixture No exposure standards has been established for this product

**Breathing Zone ppm** Breathing Zone mg/m<sup>3</sup> Component

**Personal Protection** 

Eye: Safety eyewear with splash guards or side shields to prevent eye contact is recommended when using

Hands/Feet Protective clothing. Gloves of neoprene or nitrile rubber - Industrial weight lined gauntlet

recommended.

Other Overalls, impervious clothing, barrier cream, eyewash unit, skin cleansing cream.

Practice good caution and personal cleanliness to avoid skin contact. Avoid breathing vapours of

heated materials. Wash hands thoroughly before handling food.

Respirator In confined spaces, or areas with limited ventilation where any exposure standard may be exceeded,

wear a suitable respirator

#### PHYSICAL AND CHEMICAL PROPERTIES SECTION 9.

**Appearance** White viscous liquid

Vapour Pressure Vapour Density **Boiling Point** Melt Freeze Odour рΗ

Solubility Volatile by Weight 0.5kPa 6.4 161℃ hydrocarbon n/a **Immiscible** 24

#### STABILITY AND ACTIVITY SECTION 10.

Chemical Stability Product is considered stable under normal storage and handling conditions.

**CEILING VELVET** Resene Paints Limited Page 2 of 4

Conditions to Avoid Freezing, excessive heat and changes in temperature Incompatible Materials

Hazardous decomposition product Oxides of carbon and nitrogen

Hazardous reactions Hazardous polymerisation will not occur.

### **CEILING VELVET**

## SECTION 11. TOXICOLOGICAL INFORMATION

No data available for this product

Component Oral:LD50 mg/k Dermal:LD50 mg/k Inhale:LC50 pp

## SECTION 12. HAZARDS IDENTIFICATION

Do not allow the product to enter the environment

No data available for this product

Component Fish:LC50 mg/Lt BCF:<100 Kow

## SECTION 13. DISPOSAL CONSIDERATIONS

Special precautions for landfill or incineration

Consult manufacturer for recycling options and recycle where possible

Decontaminate empty containers. Observe all label safeguards until containers are cleaned and destroyed

## SECTION 14. TRANSPORT INFORMATION

Transport only in accordance with the following regulations

UN Number 1263

Proper Shipping Name Paint related product

Subsidiary Risk Poison Schedule

Packing Group: III

Class

HAZCHEM Code 3[Y]

Special precautions for user

## SECTION 15. REGULATORY INFORMATION

Group Standard HSR002662 Surface Coatings & Colourants - Flammable

Approved Handler Not required

## SECTION 16. OTHER INFORMATION

Date of Preparation 31/03/13

Literature references MSDS's for individual raw material

**Abbreviations:** 

NOHSC National Occupational Health and Safety Commission

TWA Time weighted average STEL Short term exposure limit

CAS Numbe Chemical Abstract Service registry number

TLV Threshold limit value

Marine Pollutant Marine Pollutan

## Safety data sheets are updated frequently. Please ensure that you have a current copy

The information contained herein is based on data considered accurate and reliable to the best of our knowledge and belief as of the date compiled. However no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use hereof. Resene Paints (New Zealand) Limited assumes no responsibility for personal injury or property damage to vendors, users or third parties caused by the material. Such users or vendors assume all risks associated with the use of the material. It is the users responsibility to satisfy themselves as to the suitability and completeness of the information for their own particular use. The users must determine whether the use of the information and data is in accordance with local laws and regulations