

Safety Data Sheet



1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name: 910-LINE ARMOURSPRAY AG

Recommended Use: Powder coating. Applied by electrostatic spray.

Supplier: Dulux Powder & Industrial Coatings, a division of DuluxGroup (New Zealand) Pty Ltd
ABN 55 133 404 118
Co. 2355191

Street Address: 31B Hillside Road
Auckland, New Zealand

Telephone Number: +64 09 441 8244

Facsimile: +64 09 441 8242

Emergency Telephone: 0 800 734 607 (ALL HOURS)

2. HAZARDS IDENTIFICATION

Not classified as a Dangerous Good under NZS 5433:2007 Transport of Dangerous Goods on Land.

Based on available information, not classified as hazardous according to criteria in the HS (Minimum Degrees of Hazard) Regulations 2001.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS Number	Proportion	Risk Phrases
Synthetic polymer(s)	-	30-60%	-
Pigments	-	30-60%	-
Blocked cycloaliphatic diisocyanate adduct	-	10-<30%	-
Ingredients determined not to be hazardous	-	to 100%	-

4. FIRST AID MEASURES

Inhalation:

Remove victim from area of exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. Seek medical advice if effects persist.

Skin Contact:

If skin contact occurs, remove contaminated clothing and wash skin with running water. If irritation occurs seek medical advice.

Eye Contact:

If in eyes, wash out immediately with water. In all cases of eye contamination it is a sensible precaution to seek medical advice.

Ingestion:

Rinse mouth with water. If swallowed, give a glass of water to drink. Seek medical advice.

Medical attention and special treatment:

Treat symptomatically.

Product Name: 910-LINE ARMOURSPRAY AG
Substance No: 000000021334

Issued: 30/06/2010
Version: 5

5. FIRE FIGHTING MEASURES

Hazards from combustion products:

Combustible solid. On burning will emit toxic fumes, including those of oxides of carbon and oxides of nitrogen .

Precautions for fire fighters and special protective equipment:

Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion.

Suitable Extinguishing Media:

Fine water spray, normal foam, dry agent (carbon dioxide, dry chemical powder).

6. ACCIDENTAL RELEASE MEASURES

Emergency procedures:

If contamination of sewers or waterways has occurred advise local emergency services.

Methods and materials for containment and clean up:

Wear protective equipment to prevent skin and eye contact and breathing in dust. Work up wind or increase ventilation. Cover with damp absorbent (inert material, sand or soil). Sweep or vacuum up, but avoid generating dust. Collect and seal in properly labelled containers or drums for disposal.

7. HANDLING AND STORAGE

Precautions for safe handling: Avoid skin and eye contact and breathing in dust or oven fumes that may be formed during processing. In common with many organic chemicals, may form flammable dust clouds in air. For precautions necessary refer to Safety Data Sheet "Dust Explosion Hazards".

Conditions for safe storage: Store in a cool, dry, well ventilated place and out of direct sunlight. Store away from incompatible materials described in Section 10. Keep containers closed when not in use - check regularly for spills.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Limits: No value assigned for this specific material by the New Zealand Occupational Safety and Health Service (OSH). However, Workplace Exposure Standard(s) for constituent(s):

Nuisance dust: WES-TWA 10 mg/m³

For oven fumes:

Caprolactam Vapour: WES-TWA 5 ppm, 23 mg/m³; WES-STEL 10 ppm, 46 mg/m³

Safety Data Sheet



As published by the New Zealand Occupational Safety and Health Service (OSH).

WES - TWA (Workplace Exposure Standard - Time Weighted Average) - The eight-hour, time-weighted average exposure standard is designed to protect the worker from the effects of long-term exposure.

WES - STEL (Workplace Exposure Standard - Short Term Exposure Limits) - The 15 minute average exposure standard. Applies to any 15 minute period in the working day and is designed to protect the worker against adverse effects of irritation, chronic or irreversible tissue change, or narcosis that may increase the likelihood of accidents. The WES-STEL is not an alternative to the WES-TWA; both short-term and eight-hour, time-weighted average exposures should be determined.

These Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept to as low a level as is workable. These exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

Engineering controls:

Ensure ventilation is adequate and that air concentrations of components are controlled below quoted Exposure Standards. Before applying consult AS3754 - Safe application of powder coatings by electrostatic spraying. For electrostatic spraying, ensure continuity of earthing. Avoid generating and breathing in dusts. Use with local exhaust ventilation or while wearing dust mask. Ensure baking ovens are suitably vented to the atmosphere and that emissions meet environmental standards. Keep containers closed when not in use.

Personal Protective Equipment:

The selection of PPE is dependant on a detailed risk assessment. The risk assessment should consider the work situation, the physical form of the chemical, the handling methods, and environmental factors.

Personal Protection: E - OVERALLS, SAFETY SHOES, SAFETY GLASSES, GLOVES, DUST MASK.



Wear overalls, safety glasses and impervious gloves. Avoid generating and inhaling dusts. If excessive dust exists, wear dust mask/respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storage or re-use. Avoid breathing fumes released in baking. If risk of inhalation exists, wear organic vapour respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Powder
Colour:	Coloured
Odour:	Slight
Solubility:	Insoluble in water.
Specific Gravity:	1.1-1.6 @20°C
Relative Vapour Density (air=1):	Not applicable
Vapour Pressure (20 °C):	Not applicable

Product Name: 910-LINE ARMOURSPRAY AG
Substance No: 000000021334

Issued: 30/06/2010
Version: 5

Safety Data Sheet



Flash Point (°C):	Not applicable
Flammability Limits (%):	Not available
Autoignition Temperature (°C):	Not available
% Volatile by Weight:	<1
Solubility in water (g/L):	Insoluble
Melting Point/Range (°C):	Not available
Boiling Point/Range (°C):	Not applicable
Decomposition Point (°C):	Not available
pH:	Not applicable
Viscosity:	Not applicable
Evaporation Rate:	Not applicable

10. STABILITY AND REACTIVITY

Chemical stability:	Stable under normal conditions of use.
Conditions to avoid:	Avoid contact with foodstuffs. Avoid exposure to heat, sources of ignition, and open flame.
Incompatible materials:	Incompatible with oxidising agents.
Hazardous decomposition products:	Oxides of carbon. Oxides of nitrogen. Caprolactam.
Hazardous reactions:	Hazardous polymerisation will not occur.

11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

Ingestion:	No adverse effects expected, however, large amounts may cause nausea and vomiting.
Eye contact:	May be an eye irritant.
Skin contact:	Contact with skin may result in irritation.
Inhalation:	Breathing in dust may result in respiratory irritation. Fumes released in baking are irritant to the mucous membranes.

Long Term Effects:
No information available for the product.

Toxicological Data: No LD50 data available for the product.

12. ECOLOGICAL INFORMATION

Ecotoxicity Avoid contaminating waterways.

13. DISPOSAL CONSIDERATIONS

Product Name: 910-LINE ARMOURSPRAY AG
Substance No: 000000021334

Issued: 30/06/2010
Version: 5

Safety Data Sheet



Disposal methods:

Refer to Waste Management Authority. Dispose of material through a licensed waste contractor. Normally suitable for disposal at approved land waste site.

14. TRANSPORT INFORMATION

Road and Rail Transport

Not classified as a Dangerous Good under NZS 5433:2007 Transport of Dangerous Goods on Land.

Marine Transport

Not classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea; NON-DANGEROUS GOODS.

Air Transport

Not classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air; NON-DANGEROUS GOODS.

15. REGULATORY INFORMATION

Classification:

Based on available information, not classified as hazardous according to criteria in the HS (Minimum Degrees of Hazard) Regulations 2001.

16. OTHER INFORMATION

Reason(s) for Issue:

Revised Primary SDS
Alignment to HSNO requirements

This safety data sheet has been prepared by SH&E Shared Services.

This SDS summarises to our best knowledge at the date of issue, the chemical health and safety hazards of the material and general guidance on how to safely handle the material in the workplace. Since DuluxGroup Limited cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, assess and control the risks arising from its use of the material.

If clarification or further information is needed, the user should contact their DuluxGroup representative or DuluxGroup Limited at the contact details on page 1.

DuluxGroup Limited's responsibility for the material as sold is subject to the terms and conditions of sale, a copy of which is available upon request.