

## Thermal Ceiling and Skillion Roof

### Description

ecoinsulation® Thermal Ceiling and Skillion Roof insulation with DriTherm® technology is made using a silicone treatment that is added during manufacture to upgrade the moisture resistance of the glasswool insulation, and provide guaranteed water resistance for 50 years.

ecoinsulation® Thermal Ceiling and Skillion Roof insulation is made using:

- Up to 80% recycled glass
- ECOSE® Technology - binder with no added formaldehyde
- TwinTech® - dual forming technique for a smooth finish on both sides.



### Product Range

Product code	R-Value (m² K/W)	Lambda (W/mK)	Thickness (mm)	Width (mm)	Length (mm)	Area per pack (m²)	Pieces per pack
<b>Standard Ceiling</b>							
683700	3.6	0.044	160	430	1160	10.0	20
<b>Ceiling High Performance</b>							
683702	4.2	0.042	180	430	1160	8.5	17
683703	5.2	0.040	210	430	1160	5.5	11
779548	7.0	0.047	330	460	1200	4.4	8
<b>Skillion High Performance</b>							
683706	3.2	0.033	105	430	1160	5.5	11
779681	5.0	0.033	165	430	1160	3.0	6
779685	6.0	0.036	215	430	1160	3.5	7
781977	7.4	0.036	265	430	1160	3.0	6
<b>Perimeter batt</b>							
812472	3.4	0.032	110	580	1160	4.7	7

All dimensions are nominal.

### Technical Data

#### Water Vapour Absorption

- Less than 5% by weight.

#### Corrosion Resistance

- No greater than sterile cotton.

#### Microbial Growth

- Does not support microbial growth.

#### Fire Hazard Properties (AS/NZS 1530.3)

- Ignitability: 0, Spread of flame: 0.
- Heat Evolved: 0, Smoke Developed: 2-3.

#### Combustibility (AS 1530.1)

- Non-combustible.

### Performance

Thermal  
AS/NZS 4859.1 (2018).



Declare.



# Thermal Ceiling and Skillion Roof

## Specification Compliance

AS/NZS 4859.1 (2018) Materials used in the Thermal Insulation of Buildings and comply with the New Zealand Building Code requirements: B2 – Durability, E3 – External Moisture, F2 – Hazardous Building Materials, and H1 – Energy Efficiency.

**ecoinsulation**<sup>®</sup> glasswool is an acceptable solution in terms of the New Zealand Building Code. This product is designed for use in timber and metal frame applications in new and existing domestic and commercial buildings.

## Bio-solubility

The formulation used for **ecoinsulation**<sup>®</sup> glasswool insulation has been independently assessed to meet the requirements of the stringent Note Q standard (and is therefore consistent with the highest Australian and New Zealand industry standards), and also assessed by Knauf Insulation against NZ Work-Safe requirements. **ecoinsulation**<sup>®</sup> glasswool is classified as a non-hazardous substance in line with the NOHSC: 1008 3rd Edition.

## Environmental

**ecoinsulation**<sup>®</sup> glasswool represents no known threat to the environment and comes with GreenTag Level A certification, and Declare Red List Free label. **ecoinsulation**<sup>®</sup> glasswool has low VOC and benefits from ECOSE<sup>®</sup> Technology.

## Features and Benefits

Proven Performance

- Preferred by professional installers concerned with quality, appearance and productivity.
- Excellent acoustical properties reduce sound transmission in the home when properly installed in walls, ceiling and floor systems.

## Durability

- **ecoinsulation**<sup>®</sup> glasswool is odourless, rot proof, non-hygroscopic, does not sustain vermin and will not encourage the growth of fungi, mould or bacteria.
- DriTherm<sup>®</sup> technology - silicone treated for increased durability.

## Superior Handling

- Highly resilient insulation recovers quickly to full thickness for a snug fit and superior finished aesthetics.
- Consistent quality materials that feel good, cut easily and can be installed fast.
- Low dust for easier handling and increased productivity.

## Convenient Packaging, Easier Handling

- **ecoinsulation**<sup>®</sup> glasswool is packaged in a strong, white poly bag that offers excellent protection from abuse, dust and moisture.
- **ecoinsulation**<sup>®</sup> glasswool packages feature easy to follow installation instructions.
- MasterBag insulation units (containing multiple packs) ensure reduced handling costs with improved compression – more square metres per bag, more square metres per truck load, fewer trips to the job site and less warehouse space for storage.

## Superior Service and Support

- We are focused on providing first class customer service, producing high quality products and 'in full on time' deliveries.
- We are committed to providing a comprehensive range of relevant sales and marketing literature and web-based technical information to support specifiers and customers.

**ecoinsulation**  
energy and installation



Eco Insulation Energy  
and Installation Limited  
PO Box 217063, Botany Junction,  
Auckland, 2164



[www.ecoinsulation.co.nz](http://www.ecoinsulation.co.nz)



[products@ecoinsulation.co.nz](mailto:products@ecoinsulation.co.nz)



**0800 400 326**