

Resene Furniture and Decking Oil

Resene Furniture and Decking Oil is designed for direct application to timber decks and furniture to enhance and restore the timber colour and provide protection against water, fungi, and U.V. light.

The product is designed for annual application to keep decks and furniture in good condition and assist with water repellency.

exterior

Typical uses

- New and weathered timber
- Timber outdoor furniture

Vehicle type	Oil, resin, wax blend	Physical properties
Solvent	Hydrocarbon	
Colour	Amber	
Finish	Penetrating type	
Dry time (minimum)	24 hours	
Recoat time (minimum)	24 hours	
Coverage	Dependent on surface	
Usual no. of coats	2	
Toxicity	Contains no isocyanates or heavy metals	
Thinning and clean up	Do not thin, clean up with mineral turps	
VOC	c. 320 grams per litre (see Resene VOC Summary)	

Performance

Performance and limitations

1. Enhances the natural colour of new timber decks.
2. Enhances the look of weathered timber decks.
3. Easy application.

Limitations

1. Will not kill existing mould - use Resene Moss & Mould Killer (see [Data Sheet D80](#)).
2. Will not penetrate through existing coatings. Such areas will need excess wiping off.
3. Will lose reactivity if container is contaminated with water.
4. Will typically require maintenance annually.
5. Trafficable areas coated with this unmodified product will not comply with the Building Act Clause 1.3.3(d).

Furniture and Decking Oil

Surface preparation

Exposed timber (greater than one week)

Remove any gross contamination and semi-detached cellulose fibres. Apply Resene Moss & Mould Killer (see [Data Sheet D80](#)).

New timber

Ensure timber is dry and free from dirt, dust and loose material.

Caution

Sanding dusts from some hardwoods are considered carcinogenic and all old timber sanding dusts should be considered potentially harmful. Always wear an efficient dust mask.

Sanding dust from old lead or chromate based paints or old building materials containing asbestos may be injurious to the health if inhaled or ingested. Seek expert advice if the presence of these materials is suspected.

Application

Apply by brush, roller or spray. Saturate surface with Resene Furniture and Decking Oil. Badly weathered surfaces may take up to 3 square metres per litre; new timber will require 10-12 square metres per litre.

Always trial Resene Furniture and Decking Oil on a representative piece of timber first to ensure it gives the result you want on the actual timber you are staining.

New timber should be treated with Resene Furniture and Decking Oil before assembly. Pay special attention to the underside of decks, as they will be difficult to coat after the deck has been assembled.

All faces of the timber should be treated with special attention to end grains.

Precautions

1. Will not penetrate through existing coatings or very hard latewood bands. For best results wipe excess Resene Furniture and Decking Oil off with a dry, absorbent, lint free cloth rubbing along the grain.
2. Contains powerful fungicides. Avoid skin contact. If any skin contact occurs, wash skin thoroughly with soap and water. Do not scrub the skin.
3. FLAMMABLE - keep away from heat and open flame. Keep closed when not in use.
4. Avoid breathing vapour - use with adequate ventilation.

Please ensure the current Data Sheet is consulted prior to specification or application of Resene products. If the surface you propose to coat is not referred to by this Data Sheet, please contact Resene for clarification.

In Australia
PO Box 785, Ashmore City, Queensland 4214
Call 1800 738 383, visit www.resene.com.au
or email advice@resene.com.au

Resene
the paint the professionals use

In New Zealand
PO Box 38242, Wellington Mail Centre, Lower Hutt 5045
Call 0800 RESENE (737 363), visit www.resene.co.nz
or email advice@resene.co.nz