



PRODUCT RANGE/DIMENSIONS

Type	Thickness	Cover Width	Length	Surface
Corrugated	1.2mm	760mm	1800mm 2400mm 3000mm 3600mm 4200mm 4800mm	UV 1 Side
5 Rib TrimSpan	1.2mm	760mm	6000mm 7200mm 9000mm	UV 1 Side
Profile Metal Washers with EPDM Gaskets Multi-Purpose Roof Fasteners (Fixes to Timber & Steel)			50 Per Box	Galvanised
Multi-Purpose Wall Fasteners (35mm) with Aluminium Neo Washer (Fixes into Timber & Steel)			50 Per Box	Galvanised
Side Stitch Fasteners (Suntuf to Metal)			100 Per Box	Galvanised
Side Stitch Fasteners (Suntuf to Suntuf)			10 Per Box	Galvanised
Profile Matching Eave Filler (Male/Female Combo)				Foam (White)
Joining/ Lapping Tape	1mm	25mm	37m	Butyl (Light Grey)
Purlin Tape Anti-Noise	5mm	50mm	12m	Foam (White)

PANEL PHYSICAL PROPERTIES

Property	Result
Weight	1.2kg/m ²
UV Performance	Excellent*
Impact Strength	Excellent*
Withstand Hail	Excellent*
Light Transmission	85%
Service Temperature	- 50 to + 120
Expansion/Contraction	6mm/m
Minimum Recommend Pitch	5°
Fire Rating	Group 1S*
Cleaning	PSP Cleaner, or warm soapy water & soft cloth. Do not wipe when dry.

CLEAR ROOFING VS SUNTUF COMMERCIAL



SAFETY

Never walk directly on Suntuf Commercial Polycarbonate sheets. Use a board placed across at least 3 rafters to spread the load. Ensure all local safety building regulations/codes are adhered to.

HANDLING, STORAGE & MAINTENANCE

Suntuf Commercial sheets should be handled with care to avoid any unnecessary scratches prior to installation. Suntuf Commercial should be stored on a flat surface away from direct sunlight. When stacked together this will prevent possible magnification of the sun's rays through the top sheets which may cause distortion of the lower sheets. Prevent moisture getting between stored sheets.

Suntuf Commercial will continue to look new when washed down regularly with a soft sponge and warm soapy water. It is unaffected by a wide range of chemical substance however, it is important to avoid chemicals, adhesives, paint or other synthetic materials that are not compatible with polycarbonate. Please contact PSP Translucent Roofing if you are unsure.



ON THE JOB, YOU NEED SUPERIOR DAYLIGHT WITHOUT THE GLARE.

