

## Product Ordering Key and Suggested Specifications

SPIRO-LOC	300 mm	3 m	WALL THICKNESS	PROFILES	OPTION	ACCESSORIES
Galvanised Steel Rigid Duct.	Nominal Duct Diameter.	Standard Stock Length, (Others To Special Order).	0.45 mm 0.55 mm 0.95 mm	Standard Plain, Single Swage or, Double Swage.	‘Insulated.’	Spin Collar. Spin Connector. Duct Tape*. HVAC Tools. Duct Ties.

### Series Spiro-Loc

Lightweight plain galvanised steel construction, spirally wound ductwork, with a four ply lockseam joint, suitable for HVAC applications, concrete void forming, irrigation pipe and rubbish shutes.

Additional single, or double swages can be incorporated to improve rigidity and crushable strength.

Complies with AS 4254, AS 1530.3 and UL 181, where applicable.

All shall be Series Spiro-Loc as manufactured by Holyoake.

SPIRO-SET	300 mm	3 m	STANDARD OPTIONS AVAILABLE	ACCESSORIES
Aluminium Semi Rigid Duct.	Nominal Duct Diameter.	Standard Stock Length, (Others To Special Order).	SPU, Plain, Uninsulated. SPI-FP, Plain, Insulated. (R0.6/R1.0). or SAI-FP, Acoustic, Insulated. (R0.6/R1.0).	Spin Collar. Spin Connector. Duct Tape. HVAC Tools. Duct Ties.

### Series Spiro-Set

Lightweight aluminium construction, spirally wound corrugated ductwork, with a four ply lockseam to provide an airtight tube, suitable for HVAC applications. It can easily be cut and bent by hand and maintain the configuration required, without deforming its circular cross section.

With the inclusion of a lofted polyester blanket and a polyethylene external vapour barrier, it is available as an Insulated, or Acoustic Insulated Option.

Complies with AS 4254, AS 1530.3 and UL 181, where applicable.

All shall be Series Spiro-Set as manufactured by Holyoake.

SPIRO-FLEX	500 mm	3 m/6 m	STANDARD OPTIONS AVAILABLE	ACCESSORIES
Flexible Duct.	Nominal Duct Diameter.	Standard Stock Lengths, (Others To Special Order).	Plain, Un-insulated. Acoustic, Insulated. (R0.6/R1.0) or Plain, Insulated. (R0.6/R1.0).	Spin Collar. Spin Connector. Duct Tape. HVAC Tools. Duct Ties.

### Series Spiro-Flex

Super lightweight, compressible flexible air duct of two layer construction; two polyester tapes, one metallised, helically wound, encapsulating a spring steel wire. Suitable for use in low pressure HVAC systems.

Complies with ISO9705, AS 4254, AS 1530.3 and UL 181, where applicable.

All shall be Series Spiro-Flex as manufactured by Holyoake.

\* Not to be used as the primary sealing agent connecting rigid duct to rigid duct.