

ULLTRACLAD[®] Vertical Weatherboard Cavity System

Technical Statement (PTS)

Product Description and Use

The **ULLTRACLAD[®]** Vertical Weatherboard Cavity System is a cavity-based, inter-locking powder coated aluminium weatherboard system. It is designed to be used as an external wall cladding system for residential and light commercial type buildings where domestic construction techniques are used.

The system includes vertically fixed **ULLTRACLAD[®]** Shadoline, Infinity and Shado-100 weatherboards, cavity battens, internal and external corner mouldings, starter strips, board jointers, board locators, joinery flashings and accessories.

The system incorporates a primary and secondary means of weather resistance (first and second line of defence) against water penetration by separating the cladding from the external wall framing with a nominal 20 mm cavity.

New Zealand Building Code (NZBC)

The **ULLTRACLAD[®]** Vertical Weatherboard Cavity System, if designed, used, installed and maintained in accordance with the statements and conditions of BRANZ Appraisal No. 796 (2013) and the Technical Literature, will meet the following provisions of the NZBC:

Clause B1 STRUCTURE: Performance B1.3.1, B1.3.2 and B1.3.4. The Ulltraclad[®] Vertical Weatherboard Cavity System meets the requirements for loads arising from self-weight, wind and impact [i.e. B1.3.3 (a), (h) and (j)].

Clause B2 DURABILITY: Performance B2.3.1 (b), 15 years and B2.3.2.

Clause E2 EXTERNAL MOISTURE: Performance E2.3.2.

Clause F2 HAZARDOUS BUILDING MATERIALS: Performance F2.3.1.

The **ULLTRACLAD[®]** Vertical Weatherboard Cavity System is an Alternative Solution in terms of New Zealand Building Code compliance.

Evidence of compliance

Ullrich Aluminium Co Ltd provides this PTS to demonstrate that it has met its responsibilities under s14G of the Building Act. Ullrich Aluminium Co Ltd is able to support claims of performance, based on the technical evidence provided within BRANZ Appraisal

[No. 796 \(2013\) Ulltraclad[®] Vertical Weatherboard Cavity System](#)

Scope of use

The **ULLTRACLAD[®]** Vertical Weatherboard Cavity System is suitable for use as an external wall cladding for buildings within the following scope:

- the scope limitations of NZBC Acceptable Solution E2/AS1, Paragraph 1.1; and,
- constructed with timber framing complying with the NZBC; and,
- with a risk score of 0-20, calculated in accordance with NZBC Acceptable Solution E2/ AS1, Table 2; and,
- situated in NZS 3604 Wind Zones up to, and including Extra High.

The **ULLTRACLAD**[®] Vertical Weatherboard Cavity System also meets the requirements for weathertightness and structural wind loading when used as an external wall cladding system for buildings within the following scope:

- the scope limitations of NZBC Acceptable Solution E2/AS1, Paragraph 1.1 with regards to building height and floor plan area; and,
- constructed with timber framing complying with the NZBC; and,
- situated in specific design wind pressures up to a maximum design differential ultimate limit state (ULS) of 2.5 kPa.

The **ULLTRACLAD**[®] Vertical Weatherboard Cavity System must only be installed vertically on vertical, flat surfaces.

The **ULLTRACLAD**[®] Vertical Weatherboard Cavity System is suitable for use with aluminium window and door joinery that is installed with vertical jambs and horizontal heads and sills. *(It is expected that the joinery will meet the requirements of NZS 4211 for the relevant Wind Zone, or wind pressure.)*

Technical Literature

The following Technical Literature must be followed to ensure compliance when the **ULLTRACLAD**[®] Vertical Weatherboard Cavity System is used.

Technical Drawings

- UA6975 SHADOLINE VERTICAL DETAILS VER 8
- UA7401 INFINITY VERTICAL DETAILS VER 8
- UA7726 SHADO-100 VERTICAL DETAILS VER 8

Maintenance Requirements

For Maintenance information on the **ULLTRACLAD**[®] Cavity System, refer to <http://www.duluxpowdercoatings.co.nz/information/care-maintenance/>

For Further Information Contact



(NZ) HEAD OFFICE 118 WIRI STATION ROAD PO BOX 98 843 MANUKAU CITY AUCKLAND 2241 NEW ZEALAND
Tel (09) 262 6262 Ext 814 Fax (09) 262 6266 www.ullrich.co.nz



ALLEN CLEAVER
NZ BUILDING PRODUCTS MANAGER