

**Product Classification**

Type of floor covering	ISO 10581	Homogeneous sheet vinyl
Wear Class	ISO 10581	Type II
Classification (Use Area)	ISO 10874	Walling only
Warranty*	Commercial - available upon request	15 years

\*All warranties are in addition to any rights consumers may have under Australian and New Zealand consumer laws. Terms and conditions apply - for full information in respect to the scope of the commercial warranty, contact your Armstrong Flooring representative.

**Physical Properties**

Manufactured in	-	Australia
Polyurethane reinforced	-	Yes PUR
Colours (Standard)	-	13
Overall thickness	ISO 24346	2.0mm
Roll width	ISO 24341	1.5m
Roll length	ISO 24341	20m
Coverage/roll	-	30.0m <sup>2</sup>
Product weight/m <sup>2</sup>	ISO 23997	3.5kg/m <sup>2</sup>

**Installation**

	To current AS/NZS 1884 and Armstrong Flooring Installation Instructions	Full stick, reverse sheets or heat weld seams
--	---	---

**Sustainability**

GreenTag GreenRate	-	GreenRate Level A
GreenTag LCARate	-	LCARate Gold
Environmental Product Declaration	-	Yes
Best Environmental Practice PVC	-	Yes
TVOC Emissions	-	Compliant with Green Building Council low VOC emission rates

**Technical Performance**

Fire Resistance (Walls) AU	AS 5637.1 Average specific extinction area	Group 1 < 250m <sup>2</sup> /kg
Fire Resistance (Walls) NZ	ISO 5660-1 Average specific extinction area	Group 1-S < 250m <sup>2</sup> /kg
Other		
Colour fastness	ISO 105-B02, Method 3	≥ 6
Residual indentation	ISO 24343-1	≤ 0.1mm (av)
Chemical resistance	-	Good resistance
Flexibility	ISO 24344, Method A	Pass
Seam strength	ISO 16906	Pass

**Accreditation**

Manufactured under accredited ISO 9001 quality, ISO 14001 environmental and ISO 45001 OHS management systems

All specifications are current as at date of publication and may be changed without notice. For current and complete specifications please visit [armstrongflooring.au](http://armstrongflooring.au) or [armstrongflooring.co.nz](http://armstrongflooring.co.nz)

All Armstrong Flooring products must be installed in accordance with the relevant Australian and/or New Zealand applicable standards and the Armstrong Flooring Installation Instructions.

Variations may occur between samples, photographic images, and batches in terms of colour, shade, pattern or similar.