# SAFETY DATA SHEET

#### IDENTIFICATION OF THE MATERIAL AND SUPPLIER SECTION 1.

**Product Name: IMPERITE 503 BASE** 

Other Names: Medium Aluminium

Part A of a 2 pack acrylic topcoat **Recommended Use:** 

Address: 32-50 Vogel Street, Naenae, Wellington, NEW ZEALAND **Company Name:** Resene Paints Limited New Zealand

P O Box 38242, Wellington Mail Centre

(04) 577 0500 Fax: (04) 577 0600 Phone:

> Resene Paints Limited Australia 7 Production Avenue, Molendinar, Queensland 4214 Address

P O Box 785, Ashmore City, Queensland 4214

**AUSTRALIA** 

1800 738 383 **Emergency Telephone:** 

Phone

0800 737 363 Available Monday - Friday 8.00am - 4.30pm **New Zealand** 

New Zealand Poisons Centre: 0800 764 766

**Australia** 1800 738 383

Australian Poisons Centre: 131 126

SECTION 2. HAZARDS IDENTIFICATION

Hazard Classification HAZARDOUS according to NZ HSNO Regulations

Regulated under NZS5433 for land transportation

Not assigned **Risk Phrases Safety Phrases** Not assigned

Substance Classification 3.1B 6.1D 6.3B 6.4A 6.7B 6.8B 6.9B 9.1C

**Hazard Statements** Highly flammable liquid and vapour

> Harmful if swallowed Causes mild skin irritation Causes eye irritation May cause cancer

Suspected of damaging fertility or the unborn child.

May cause damage to organs through prolonged or repeated exposure.

Harmful to aquatic life

#### SECTION 3. COMPOSITION / INFORMATION ON INGREDIENT

Ingredients	%	CAS No	TWA
Dimethylbenzene	10-30	1330-20-7	217 mg/m <sup>3</sup> NZ OSH (WES) 2002
n-Butyl Acetate	10-30	123-86-4	713 mg/m <sup>3</sup> NZ OSH (WES) 1994
Naphtha petroleum, light aromatic	1-10	64742-95-6	123 mg/m³ as t NZ OSH (WES) 2002
Isobutanol	1-10	78-83-1	152 mg/m <sup>3</sup> NZ OSH (WES) 1994
Acrylic Resin	20-60	Not known	None Establish
Proprietary ingredients	1-10	various	None Establish

#### FIRST AID MEASURES ISECTION 4.

Eyes Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do so.

Continue rinsing. If eye irritation persists get medical attention/advice.

Rinse mouth. Swallowed:

IF ON SKIN: Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Skin

If skin irritation occurs get medical advice/attention.

Remove to fresh air and keep at rest in a position comfortable for breathing. Inhaled

Aggravated medical conditions caused by exposure

Chronic Health Effects Not Identified Advice to Doctor Treat symptomatically

### SECTION 5. FIRE FIGHTING MEASURES

**Extinguisher** Foam, Carbon Dioxide, Dry Chemical

Hazards from combustion products

Special protective precautions and equipment for firefighters

Fire/Explosion Hazard Auto Ingnition Temperature Lower Explosion Limit Upper Explosion Limit

Hazchem Code Flash Point 421°C 1.7% 7.6%

3[Y]E 22°C

## SECTION 6. ACCIDENTAL RELEASE MEASURES

### **Emergency Procedures**

Keep spectators away and avoid breathing dust or vapours

#### Methods and materials for containment and clean up

Minor Spills Use absorbent clean up materials, such as fire retardant treated sawdust or diatomaceous earth.

Keep spills (and as much as possible cleaning runoffs) out of municipal sewers and waterways.

Wear protective clothing and breathing apparatus.

Sweep up.

Place in separate container for disposal or recovery.

Clean up spills immediately.

Major Spills Dike and contain spill with inert materials (eg. Sand).

Keep spills (and as much as possible cleaning runoffs) out of municipal sewers and open bodies of water.

Restrict access to area. No smoking or naked lights.

Clear area of personnel and move upwind.

Alert Fire Brigade and tell them location and nature of hazard.

Consider evacuation (or protect in place).

Stop leak if safe to do so.

Collect recoverable product into labelled containers for recycling.

## SECTION 7. HANDLING AND STORAGE

**Precautions for safe handling** Avoid damaging containers. Keep lids on containers when not in use Conditions for safe storage including any incompatibilities Not identified

Storage Temperatures Min 1°C Max 40°C

# SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

National exposure

standards for mixture

No exposure standards has been established for this product

Component Breathing Zone ppm Breathing Zone mg/m<sup>3</sup>

### **Personal Protection**

Eye: Safety eyewear with splash guards or side shields to prevent eye contact is recommended when using

any paint.

Hands/Feet Protective clothing. Gloves of neoprene or nitrile rubber - Industrial weight lined gauntlet

recommended.

Other Overalls, impervious clothing, barrier cream, eyewash unit, skin cleansing cream.

Practice good caution and personal cleanliness to avoid skin contact. Avoid breathing vapours of

heated materials. Wash hands thoroughly before handling food.

**Respirator** None required

# SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance Coloured viscous liquid

Odour pH Vapour Pressure Vapour Density Boiling Point Melt Freeze

Ester n/a 1.33 kPa 4.0 126°C -77°C Solubility Volatile by Weigh

**Immiscible** 

42

# SECTION 10. STABILITY AND ACTIVITY

Chemical Stability Product is considered stable under normal storage and handling conditions.

Conditions to Avoid Freezing, excessive heat and changes in temperature

IMPERITE 503 BASE Page 2 of 4 Resene Paints Limited

Incompatible Materials
Hazardous decomposition product Oxides of carbon and nitrogen
Hazardous reactions Hazardous polymerisation will not occur.

#### **IMPERITE 503 BASE**

### SECTION 11. TOXICOLOGICAL INFORMATION

No data available for this product

Component Oral:LD50 mg/k Dermal:LD50 mg/k Inhale:LC50 pp

## SECTION 12. HAZARDS IDENTIFICATION

No data available for this product

Do not allow the product to enter the environment

Component Fish:LC50 mg/Lt BCF:<100 Kow

### SECTION 13. DISPOSAL CONSIDERATIONS

Special precautions for landfill or incineration

Consult manufacturer for recycling options and recycle where possible

Decontaminate empty containers. Observe all label safeguards until containers are cleaned and destroyed

### SECTION 14. TRANSPORT INFORMATION

Transport only in accordance with the following regulations

UN Number 1263

Proper Shipping Name Paint related material

Subsidiary Risk Poison Schedule

Packing Group: II

Class 3

HAZCHEM Code 3[Y]E

Special precautions for user

### SECTION 15. REGULATORY INFORMATION

Group Standard HSR002669 Surface Coatings & Colourants - Flammable, Toxic[6.7]

Approved Handler Class 3.1B required for quantities in excess of 250Lt (in container of greater than 5 L capacity) or 500Lt (in containers of up to and including 5Lt capacity)

### SECTION 16. OTHER INFORMATION

Date of Preparation 31/10/2010

Literature references MSDS's for individual raw material

Abbreviations:

NOHSC National Occupational Health and Safety Commissio

TWA Time weighted average STEL Short term exposure limit

CAS Numbe Chemical Abstract Service registry number

TLV Threshold limit value

Marine Pollutant Marine Pollutant

#### Safety data sheets are updated frequently. Please ensure that you have a current copy

The information contained herein is based on data considered accurate and reliable to the best of our knowledge and belief as of the date compiled. However no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use hereof. Resene Paints (New Zealand) Limited assumes no responsibility for personal injury or property damage to vendors, users or third parties caused by the material. Such users or vendors assume all risks associated with the use of the material. It is the users responsibility to satisfy themselves as to the suitability and completeness of the information for their own particular use. The users must determine whether the use of the information and data is in accordance with local laws and regulations.