

**MASONS WRAP STRAP**  
**BUILDING PRODUCT**  
**INFORMATION SHEET**



**MASONS**  
Designed Smart, Built Tough.

V2.0 February 2024

---

**PRODUCT NAME**

Masons Wrap Strap

---

**PRODUCT LINE**

Masons Wrap accessories

---

**PRODUCT DESCRIPTION AND ITS INTENDED USE:**

Masons Wrap Strap is 0.55mm thick extruded strapping embossed both sides made from recycled polypropylene.

Wrap strap is used to restrain flexible wall underlays such as Barricade FR from billowing into the drained cavity. Wrap strap may also be used to support roof underlay such as the Masons VHP roof underlay as an alternative to mesh in certain situations or pitches.

Wrap Strap may be used as hand strapping for packaging purposes.

---

**PRODUCT IDENTIFIERS**

WRAPST19x300	19mm x 300Lm
WRAPST25x250	25mm x 250Lm

---

**PLACE OF MANUFACTURE**

China

---

**MANUFACTURER: Legal And Trading Name**

Masons Plastabrick Ltd

---

**IMPORTER: Legal And Trading Name**

Company	Masons NZ Ltd
---------	---------------

Address	18A David McCathie Place, Silverdale, Auckland
---------	--

Phone number	0800 522 533
--------------	--------------

Email Address	info@mpb.co.nz
---------------	----------------

Website	mpb.co.nz
---------	-----------

NZBN	9429031171090
------	---------------

---

**RELEVANT BUILDING CLAUSE**

E2/AS1 9.1.7 F, 9.1.8.5 - b), also 8.1.5.1 & NZS2295.2206 A3.2.1

B2 Durability 15-50 years behind cladding or roofing.

F2 Hazardous Materials - no hazardous materials



---

### STATEMENT ON HOW THE PRODUCT IS EXPECTED TO CONTRIBUTE TO COMPLIANCE

Masons Wrap Strap is used to restrain pliable wall underlays commonly called house wrap from billowing into the drained cavity in accordance with E2/AS1 9.1.7 F, 9.1.8.5 - b), also 8.1.5.1 & NZS2295.2206 A3.2.1

Wrap strap may also be used as an alternative to octagonal mesh to support roof underlay in residential or similar roof construction where required 8.1.5.1 & NZS2295.2206 A3.2.1

---

### LIMITATIONS ON THE USE OF THE PRODUCT

- Wrap Strap should not be permanently exposed to UV light, it is should to covered by cladding as part of the roof or wall assembly.
- Wrap strap is not typically used in commercial or industrial roofs where safety mesh is required or preferred.

---

### INSTALLATION REQUIREMENTS

Wrap Strap is installed at 300mm intervals over the wall underlay, pulled taut and typically fixed to studs with galvanised or SS staples. Propriety fixings such as cap nails or pressed metal underlay fasteners (little grippers) may also be used if preferred. For roof underlay the Wrap Strap is fixed taut at 300mm intervals to the roof framing first prior to rolling out and fixing the roof underlay.

---

### MAINTENANCE REQUIREMENTS

None.

---

### IS THE BUILDING PRODUCT/BUILDING PRODUCT LINE SUBJECT TO WARNING OR BAN UNDER SECTION 26 OF THE NEW ZEALAND BUILDING CODE?

No.

---