

## PRODUCT DATA SHEET

# Sika AnchorFix<sup>®</sup>-2020

High performance professional anchoring adhesive

## DESCRIPTION

Sika AnchorFix<sup>®</sup>-2020 is an epoxy acrylate, resin based, 2-part, thixotropic, fast curing, anchoring adhesive for anchoring threaded rods and reinforcing bars in both cracked and un-cracked concrete. For use in normal/moderate climate conditions.

## USES

Sika AnchorFix<sup>®</sup>-2020 may only be used by experienced professionals.

Fast curing anchoring adhesive for fixing of non-expanding anchors in the following:

### Structural work

- Rebar / steel reinforcement anchoring in new and refurbishment works
- Threaded rods
- Bolts and special fastening / fixing systems

### Metalwork, carpentry

- Handrails, balustrades and supports
- Railings
- Window and door frames

### Substrates

- Concrete (cracked and un-cracked)
- Solid masonry
- Wood
- Hard natural stone
- Solid rock

## CHARACTERISTICS / ADVANTAGES

- Fast curing
- Standard sealant guns can be used
- High load capacity
- Good adhesion to substrate
- Suitable for cracked concrete
- Suitable for contact with drinking water
- Seismic tested (C1 & C2)
- Non-sag including overhead
- Styrene-free
- Low emissions
- Low wastage

## APPROVALS / STANDARDS

- Post-Installed Adhesive Anchors in Concrete Elements IBC/IRC, Sika AnchorFix<sup>®</sup>-2020, IAPMO UES, Evaluation report No. 601
- ETA-22/0893. For details see accompanying documents, EAD 330499-01-0601: 2018, 1020: Bonded injection type anchor for use in cracked and un-cracked concrete
- ETA-22/0892. For details see accompanying documents, EAD 330087-01-0601: 2018,1020: Post installed rebar connections
- Certificate for contact with drinking water NSF/ANSI/CAN 61 File No. K-8319

## PRODUCT INFORMATION

Packaging	300 ml standard cartridge	12 cartridges per box pallet: 75 boxes
Shelf Life	12 months from date of production	
Storage Conditions	The product must be stored in original, unopened and undamaged sealed packaging in dry conditions at temperatures between +5 °C and +25 °C. Always refer to packaging.	
Colour	Part A	White
	Part B	Black
	A+B mixed	Grey
Density	~1.70 kg/l (Part A) ~1.55 kg/l (Part B) ~1.69 kg/l (A+B mixed)	

## SYSTEM INFORMATION

System Structure	Ancillary products: <ul style="list-style-type: none"> <li>▪ Sika AnchorFix® Cleaning Pump</li> <li>▪ Sika AnchorFix® Hole Cleaning Brushes Steel</li> <li>▪ Sika AnchorFix® Static Mixers -Nozzles</li> </ul>	
------------------	--	--

## TECHNICAL INFORMATION

Service Temperature	Long term	-40 °C min. / +50 °C max	(ETAG 001, Part 5)
	Short term (1-2 hours)	+80 °C	

## APPLICATION INFORMATION

Mixing Ratio	Part A : Part B = 10 : 1 by volume		
Layer Thickness	~5 mm max.		
Sag Flow	Non-sag, including overhead		
Product Temperature	+5 °C min. / +30 °C max.		
Ambient Air Temperature	+5 °C min. / +30 °C max.		
Dew Point	Beware of condensation. Substrate temperature during application must be at least +3 °C above dew point.		
Substrate Temperature	+5 °C min. / +30 °C max.		
Curing Time	<b>Temperature</b>	<b>Open time - T<sub>gel</sub></b>	<b>Curing time - T<sub>cur</sub></b>
	+30 °C – +35 °C	2 minutes	30 minutes
	+25 °C – +30 °C	4 minutes	40 minutes
	+20 °C – +25 °C	5 minutes	50 minutes
	+15 °C – +20 °C	6 minutes	75 minutes
	+10 °C – +15 °C	8 minutes	85 minutes
	+5 °C – +10 °C*	10 minutes	145 minutes

\*Minimum cartridge temperature = +5 °C

## BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may

vary due to circumstances beyond our control.

## FURTHER DOCUMENTS

## LIMITATIONS

- Natural stone and solid rock properties vary particularly with regard to strength, composition and porosity. For each application, the suitability of Sika AnchorFix®-2020 must be tested for bond strength, surface staining and discoloration by first applying the product to a sample area before full project application.

## ECOLOGY HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety-related data.

## APPLICATION INSTRUCTIONS

### SUBSTRATE QUALITY


Mortar and concrete must be at the required design strength.

Substrate tensile / compressive strengths (concrete, masonry, natural stone) must be confirmed by testing. The anchor hole must always be clean, dry, free from oil and grease etc.


Loose particles must be removed from the holes. Threaded rods and rebar's must be cleaned thoroughly and free from dirt, oil, grease, corrosion products or any other substances and particles which could affect adhesion.

### MIXING


#### Getting the cartridge ready: 300ml




1. Unscrew the cap



2. Cut the film



3. Screw on the static mixer




4. Place the cartridge into the gun and start application

## APPLICATION METHOD / TOOLS


### Anchors in solid masonry/concrete




1. Drill hole with an electric drill to the diameter and depth required. Drill hole diameter must be in accordance with anchor size




2. The drill hole must be cleaned with oil free compressed air using an air lance, pressure: 6 Bar (90 psi). Start from the bottom of the hole and clean minimum 2 x until return air stream is free of dust




3. The drill hole must be thoroughly cleaned with the special steel brush (brush at least 2x). The diameter of the brush must be larger than the diameter of the drill hole




4. The drill hole must be cleaned again as stage 2




5. The drill hole must be thoroughly cleaned again as stage 3




6. The drill hole must be cleaned again as stage 2 & 4




7. Pump gun at least 2 x until both parts are extruded as a one consistent colour. Do not use this material. Release the gun pressure and clean the static mixer opening with a cloth



8. Inject the adhesive into the drill hole, starting from the bottom and slowly pull out the static mixer while extruding the resin into the hole. Avoid entrapping air. For deep holes use extension tubing



9. Insert the anchor with a rotary motion into the filled drill hole within the adhesive open time. Some of the adhesive must flow out of the hole



10. During the resin hardening time the anchor must not be moved or loaded

Important Note: Anchors in hollow blocks: Use Sika AnchorFix®-1.

## CLEANING OF TOOLS

Clean all tools and application equipment with Sika® Colma Cleaner immediately after use. Hardened material can only be removed mechanically.

## LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

## LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request. It may be necessary to adapt the above disclaimer to specific local laws and regulations. Any changes to this disclaimer may only be implemented with permission of Sika® Corporate Legal in Baar.

**Sika (NZ) Limited**  
85-91 Patiki Road  
Avondale, Auckland 1026  
New Zealand  
0800 745 269  
www.sika.co.nz



**Product Data Sheet**  
Sika AnchorFix®-2020  
April 2024, Version 01.02  
020205010020000012

SikaAnchorFix-2020-en-NZ-(04-2024)-1-2.pdf