

Powerful centrifugal fan with

# TWO BOOST LEVELS & LOW SPEED OPTION

- Boost level for KITCHEN installation
- Boost level for LAUNDRY installation
- Low speed for LONG TERM TRICKLE ventilation

- G4 and Healthy Homes compliant for kitchen extract ventilation levels
- Front grille with removable dishwasher safe metal grease filter
- Plate fascia and fine filter kit (DCT4529) available as front grille alternative





#### **COMPLIANCE**

While it is 100mm in diameter the Cucina Kitchen fan, when it is used in a through wall application to a weatherproof cowl (DCT0018), exceeds and complies with the following regulations on the basis of its high pressure centrifugal fan, airflow performance, when installed to kitchen boost. Airflow performance for continuous operation on low speed is also provided.

# Minimum Installed System Airflow Requirements - all exceeded by Cucina

Regulation	Speed	Kitchen Fans	Bathroom Fans
Healthy Homes Residential Tenancy	Kitchen Boost	50 l/s	25 l/s
New Zealand Building Code G4 Ventilation AS1 - Version 4	Kitchen Boost	50 l/s	25 l/s
	Low Speed	12 l/s	10 l/s

#### **PERFORMANCE**



#### **TECHNICAL SPECIFICATIONS**

#### **Kitchen Installations - High Speed**

Supply 220-240V AC 50Hz
Max. Fan Watts 60W
Max. Fan Pressure 236Pa
Fan Performance 73 l/s, 263m³/hr
free air performance

Specific Fan Power0.82 W/l/sSound Level52 dB(A)Ducting100mmSwitchingPull cord

## **Laundry Installations - Medium Speed**

Supply 220-240V AC 50Hz
Max. Fan Watts 41W
Max. Fan Pressure 140Pa
Fan Performance 39 l/s, 140m³/hr

free air performance

Specific Fan Power 1.05 W/l/s Sound Level 38 dB(A) Ducting 100mm Switching Pull cord

## **Optional Accessories**




DCT4529
Plate Fascia
and Fine Filter Kit
(order separately)




DCT4562 Replacement Washable Metal Grease Filter (order separately)

#### WIRING DIAGRAM



# **DIMENSIONS (mm)**





Complies with AS/NZS Standards
Specifications are subject to change without notice