
Chesterfield™



Product Classification

Type of floor covering	ISO 10582	Luxury Vinyl Plank
Wear Class	ISO 10582	Type I
Classification (Use Area)	ISO 10874	Domestic: 23 (Heavy) Commercial: 31 (Moderate)
Warranty*	Residential Commercial - available upon request	15 years 3 years

^{*}All warranties are in addition to any rights consumers may have under Australian and New Zealand consumer laws. Terms and conditions apply - for full information in respect to the scope of the residential warranty, please see armstrongflooring au or armstrongflooring conz or contact our Head Office. For the commercial warranty, contact your Armstrong Flooring representative.

Physical Properties

Surface Treatment		PUR > 48% clear	
Colours (Standard)		12	
Overall thickness (mm)	ISO 24346	2.0	
Wear layer (mm)	ISO 24340	0.30	
Bevel		Micro	
Dimensions (mm)	ISO 24342	1219 x 184	
Planks/carton		20	
m²/carton		4.49	
m²/pallet		314.3	
kg/carton		16.0	

Installation

To current AS/NZS 1884 and Armstrong Flooring Installation Instructions - LVT/P

Sustainability

Global GreenTag	GreenRate Level A
TVOC Emissions	Compliant with Green Building Council low emitting VOC emission rates

Technical Performance

AS 4586 Wet Pendulum (Appendix A)	P3	
AS ISO 9239-1 Critical Radiant Flux (CHF Value) Smoke Development Rate	≥ 4.5kW/m² ≤ 750%.min	
ISO 105-B02, Method 3	≥ 6	
	Wet Pendulum (Appendix A) AS ISO 9239-1 Critical Radiant Flux (CHF Value) Smoke Development Rate	Wet Pendulum (Appendix A) P3 AS ISO 9239-1 Critical Radiant Flux (CHF Value) ≥ 4.5kW/m² Smoke Development Rate ≤ 750%.min

Accreditation

Manufactured under accredited ISO 9001 quality, ISO 14001 environmental and ISO 45001 OHS management systems

All specifications are current as at date of publication and may be changed without notice. For current and complete specifications please visit armstrongflooring au or armstrongflooring.conz
All Armstrong Flooring products must be installed in accordance with the relevant Australian and/or New Zealand applicable standards and the Armstrong Flooring Installation Instructions.

Variations may occur between samples, photographic images, and batches in terms of colour, shade, pattern or similar.

