

**1. Identification of Substance & Company**

Product	
Product name	FIRTH MASONRY
Other names	Firth Masonry Block, Firth Paving, Firth Segmental retaining wall, Firth Brick veneer range
Product code	NA
HSNO approval	This product is a manufactured article and does not require HSNO approval. However the following MSDS is relevant for fine dust created whilst working with the Masonry. The relevant approval code for MASONRY is: HSR002545
Approval description	Construction Products (Toxic [6.7A]) Group Standard 2006
UN number	Not allocated
Proper Shipping Name	NA
Packaging group	NA
Hazchem code	1T (recommended)
Uses	Masonry block Paving products Segmental retaining wall products Building veneer products and specialist detail profiles

Company Details

Company	Firth Industries
Address	585 Great South Rd, Penrose PO Box 99904, Newmarket, 1149 Auckland, New Zealand
Telephone	+64-9- 583 2100
Website	www.firth.co.nz

Emergency Telephone Number: 0800-764 766**2. Hazard Identification****Hazard Classifications**

FIRTH MASONRY is a manufactured article. Dust created when using this product has been approved under the Hazardous Substances and New Organisms Act (HSNO, Approval HSR002545), and is classified as follows:

Classes:

- 6.3A skin irritant
- 8.3A eye corrosive
- 6.7A known carcinogen (contains crystalline silica)
- 6.9A known human target organ toxicant (may cause silicosis and related effects to the lungs)
- 9.1D harmful to the aquatic environment

SYMBOLS**DANGER****Other Classifications**

There are no other classifications that are known to apply.

**Hazard and Precautionary Statements**

Hazard Any health effects will be from dust produced as a result of cutting, chasing, drilling, sanding and grinding. Handling of bricks during normal use such as unloading and bricklaying is unlikely to generate significant fine dust.

The masonry dust has the following hazard phrases:

Causes skin irritation

Causes serious eye damage.

May cause cancer.

Causes damage to organs through prolonged or repeated exposure.

Harmful to aquatic life.

Precautionary

Keep out of reach of children.

Read label before use.

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Do not eat, drink or smoke when using this product.

Wash hands thoroughly after handling.

Wear protective gloves/eye protection/face protection.

Avoid breathing dust.

Contaminated work clothing should not be allowed out of the workplace.

Avoid release to the environment. Collect spillage.

Further precautionary statements can be found in Section 4 – First Aid.

3. Composition / Information on Ingredients

Component	CAS/ Identification	Class for ingredient(s)	Conc (%)
Cement	65997-15-1	8.3A, 6.3A, 6.7A, 6.9A, 9.1D	10-70
Aggregates (may include traces of crystalline silica)	mixture	6.7A, 6.9A	80-90
Sand (may contain traces of silica quartz)	NA	6.7A, 6.9A	10-60
Metal Oxides	mixture	mixture	3-6

May contain one or more of the following ingredients:

Component	CAS/ Identification	Class for ingredient(s)	Conc (%)
Hexavalent Chromium	1333-82-0	5.1.1B, 6.1B, 6.5A, 6.5B, 6.6A, 6.7A, 6.8A, 6.9A, 8.1A, 8.2B, 8.3A, 9.1A, 9.2B, 9.3B	<0.01
Crystalline Silica (contained in cement, sand and aggregates)	14808-60-7	6.7A, 6.9A	0-5

This is a commercial product whose exact ratio of components may vary. Trace quantities of impurities are also likely.

Note: classifications for ingredients are confirmed through EPA records where available. If unconfirmed, and based on hazardous property information, the classifications are indicated in *italics*.

4. First Aid**General Information**

You should call the National Poisons Centre if you feel that you may have been harmed, burned or irritated by this product. The number is 0800 764 766 (0800 POISON) (24 hr emergency service).

If medical advice is needed, have this SDS, product container or label at hand. If exposed or concerned: Get medical advice/attention.

Recommended first aid facilities

Ready access to running water is required. Accessible eyewash. Emergency shower, hand wash, soap..

Exposure**Swallowed**

IF SWALLOWED: Do NOT induce vomiting. Rinse mouth. Contact a doctor if you feel unwell.

Eye contact

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Apply continuous irrigation with water for at least 15 minutes holding eyelids apart. Immediately call a POISON CENTER or doctor.

**Skin contact**

IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.

Inhaled

IF INHALED: If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. If patient is unconscious, place in the recovery position (on the side) for transport and contact a doctor. If experiencing respiratory symptoms: Immediately call a POISON CENTER or doctor.

Advice to Doctor

Treat symptomatically. See Section 11 for information on potential long term health effects from exposure to very fine crystalline silica dust.

5. Firefighting Measures

Fire and explosion hazards:

There are no specific risks for fire/explosion for this chemical. It is non-combustible. Not applicable.

Suitable extinguishing**substances:****Unsuitable extinguishing**

Unknown.

substances:**Products of combustion:**

Product does not burn. Masonry dust may form irritating atmosphere. Contaminated water will be strongly alkaline.

Product may decompose in a fire and produce toxic or corrosive fumes.

Protective equipment:

Self-contained breathing apparatus. Safety boots, non-flammable overalls, gloves, hat and eye protection.

Hazchem code:

1T (recommended)

6. Accidental Release Measures

Containment

If greater than 1000kg (dust) is stored, secondary containment is required to prevent harm to the aquatic environment. Emergency plans to manage any potential spills must be in place. Prevent any spillage from spreading or entering soil, waterways or drains.

Emergency procedures

In the event of large spillage (>100kg) of the dry or wetted mixture alert the fire brigade to location and give brief description of hazard.

Wear protective equipment to prevent skin, eye and respiratory exposure. Clear area of any unprotected personnel. Contain spill. Prevent by whatever means possible any spillage from entering drains, sewers, or water courses. Do not wash residues down the drain.

Clean-up method

Collect product avoiding any dust formation, and seal in properly labelled containers or drums for disposal. If contamination of crops, sewers or waterways has occurred advise local emergency services.

Disposal

Sweep and collect recoverable material into labelled containers for recycling or salvage. Recycle containers wherever possible. This material may be suitable for approved landfill. Dispose of only in accord with all regulations.

Precautions

The dust may form irritating atmosphere. Contaminated water will be strongly alkaline. Do not allow contaminated water to enter the environment.

Wear protective equipment to prevent skin and eye contamination and the inhalation of dust. Work up wind or increase ventilation.

7. Storage & Handling

Storage

Generally product (bricks) are stacked on pallets and stored in a cool dry place. Avoid storage of harmful substances with food.

Handling

Avoid contact with incompatible substances as listed in Section 10.

During the manual handling of products please lift carefully - corners are sharp.

Minimise dust generation and accumulation. See section 8 with regard to personal protective equipment requirements. Avoid skin and eye contact and inhalation of masonry dust.



8. Exposure Controls / Personal Protective Equipment

Workplace Exposure Standards

A workplace exposure standard (WES) has not been established by the NZ Department of Labour for this product. There is a general limit of $10\text{mg}/\text{m}^3$ for dusts and mists when limits have not otherwise been established.

NZ Workplace Exposure Stds (OSH 2011)	Ingredient	WES-TWA	WES-STEL
	Cement	$10\text{mg}/\text{m}^3$ (as nuisance dust)	no data
	Aggregates	See crystalline silica	no data
	Crystalline Silica	$0.2\text{mg}/\text{m}^3$ (quartz, respirable dust) $0.1\text{mg}/\text{m}^3$ (cristobalite, respirable dust)	no data

Engineering Controls

In industrial situations, it is expected that employee exposure to hazardous substances will be controlled to a level as far below the WES as practicable by applying the hierarchy of control required by the Health and Safety in Employment Act 1992 (HSE). Exposure can be reduced by process modification, use of local exhaust ventilation, capturing substances at the source, or other methods. If you believe air borne concentrations of mists, dusts or vapours are high, you are advised to modify processes or increase ventilation.

Personal Protective Equipment

Eyes



Protect eyes with goggles, safety glasses or full face mask. Avoid wearing contact lenses.


Skin



Avoid repeated or prolonged skin contact. Wear overalls, waterproof boots and impervious alkali-resistant gloves (e.g., nitrile, PVC, rubber, neoprene). Tuck overalls inside boots and seal with duct tape to reduce risk of masonry dust entering boots.



Remove protective clothing and wash exposed areas with soap and water prior to eating, drinking or smoking. Take special care to ensure that cuts/abrasions or irritated skin are not exposed to this product.



It is important that skin is also covered when masonry dust is created (e.g., sanding, grinding, crushing or cutting masonry). The dust may also irritate and/or damage the skin.



Respiratory



To prevent irritation a well fitted dust mask should be used (this is not recommended when exposure is close to the WES). A fine particulate half or full face respirator with an effective seal is recommended when airborne concentrations approach the WES (section 8). If sanding, grinding, crushing or cutting masonry, it is possible that the silica dust WES will be exceeded hence a respirator will be required. If during exposure to a concentrated aqueous solution/slurry, dust and mist is likely, a full face respirator with a particulate filter is recommended.

WES Additional Information

Not applicable



9. Physical & Chemical Properties

Appearance	Physically stable pressed, machined form semi dry, no slump concrete brick. Colour may vary from terracotta, grey, brown and blue.
Odour	none
pH	not applicable for dry product, >11 for wetted masonry dust.
Vapour pressure	not applicable
Viscosity	no data
Boiling point	not applicable
Volatile materials	no data
Freezing / melting point	no data
Solubility	insoluble in hardened state, slightly soluble in wet state to form alkaline solution (pH >11)
Specific gravity / density	1600-2300kg/m ³
Flash point	not applicable
Danger of explosion	no data
Auto-ignition temperature	no data
Upper and lower flammable limits	not applicable
Corrosiveness	May be corrosive when mixed with water.

10. Stability & Reactivity

Stability	This product is unlikely to react or decompose under normal storage conditions. This product will not undergo polymerisation reactions.
Conditions to be avoided	Containers should be kept closed in order to avoid contamination.
Incompatible groups	Strong acids.
Substance Specific Incompatibility	Masonry dissolves in hydrofluoric acid producing corrosive silicon tetrafluoride gas. Silicates react with powerful oxidizers such as fluorine, chlorine, trifluorides, and oxygen difluoride.
Hazardous decomposition products	Does not readily decompose. Respirable dust particles may be generated when masonry is sawed, drilled, sanded or grinded.
Hazardous reactions	Will not polymerise

11. Toxicological Information

Summary

Masonry dust or wet masonry dust is known to harm the skin and eyes. There are also links between exposure to masonry dust (e.g., construction) and increased rates of silicosis.

Where available, toxicological data for ingredients has been researched and data for the mixture calculated. The results of these calculations are presented below.

Supporting Data

Acute	Oral	The estimated LD ₅₀ (oral, rat) for the mixture is > 5,000 mg/kg. Ingestion of this product may cause gastrointestinal irritation.
	Dermal	The estimated LD ₅₀ (dermal, rat) for the mixture is > 5,000 mg/kg.
	Inhaled	The estimated LC ₅₀ (inhalation, rat) for the mixture is >5 mg/L (dust mist). Short term (acute) silicosis (see "systemic" below) can also occur with one-off exposures to extremely high levels of fine crystalline silica dust. Other short term effects include irritation, choking and difficulty breathing.
	Eye	Contact with masonry dust can cause effects ranging from irritation to serious eye damage/burns and blindness. The pH of the wet masonry dust is >11. Note: the level of irritation/damage is dependent on the quantity of the dust, the pH, and the length of time exposed. E.g., if dust is washed out of the eye immediately, effects will be minor. However, if dust is left in contact with the eye, serious damage/blindness could result.
	Skin	Dust may cause irritation – particularly in hot conditions or when sweating. Brief exposure to the skin (i.e., washed off immediately) will result in irritation. However, if the masonry dust is left on the skin for an extended time (e.g., if inside boots or absorbed through overalls), burns to the skin are possible. Thickening of the skin and/or rash is also possible.



Chronic	Sensitisation	There is evidence that chromium present in some cement mixtures may induce occupational asthma and skin sensitisation (allergic reactions). This mixture contains less than 0.01% hexavalent chromium and hence is not considered sensitising.
	Mutagenicity	No ingredient present at concentrations > 0.1% is considered a mutagen.
	Carcinogenicity	This mixture does contain crystalline silica. Crystalline silica inhaled in the form of quartz or cristobalite from occupational sources is carcinogenic to humans (IARC Group 1). The mixture triggers 6.7A classification (confirmed carcinogen). The carcinogenicity of silica is related to long term (e.g., 10 years) inhalation of very fine particulate (e.g., from sand blasting or dry cutting of masonry). Carcinogenicity of silica appears linked to development of silicosis (see systematic below) followed by complications and, eventually lung cancer
	Reproductive / Developmental	No data for mixture is available. No ingredient present at concentrations > 0.1% is considered a reproductive or developmental toxicant or have any effects on or via lactation.
	Systemic	The mixture is considered to be a target organ toxicant, because of the presence of crystalline silica at greater than 1%. Crystalline silica triggers 6.9A classification if it is in the form of a fine respirable dust in an occupational (chronic exposure) setting. This is due to the development of acute silicosis which can occur following exposure to extremely high levels of fine silica dust. Silicosis is a type of pneumoconiosis – a disease of the lung that causes inflammation, scar tissue, lesions and fibrosis in the lung (alveolar). Symptoms include shortness of breath, cough, fever, loss of appetite and cyanosis (bluish skin). Silicosis can occur following prolonged exposure (e.g., 10 years) to relatively high levels of fine crystalline silica dust.
	Aggravation of existing conditions	Persons with existing lung conditions may be at a higher risk of further adverse health effects (as above). Smokers have an increased risk of lung cancer and silicosis.

12. Ecological Data

Summary

Masonry and masonry dusts are considered to be harmful in the environment when in a soluble form. This is primarily due to the high pH of the product. Lime dissolves in water to produce a highly alkaline solution that will burn and kill fish, insects and plants.

Supporting Data

Aquatic	No data for mixture is available. Using EC ₅₀ 's for ingredients, the estimated EC ₅₀ for the mixture is between 1 and 100 mg/L. This implies that masonry dust should be considered harmful in the aquatic environment. Water contaminated with this product is alkaline and should not be allowed to enter the environment.
Bioaccumulation	Not applicable
Degradability	Not applicable (predominantly natural products)
Soil	No data available for the mixture. The soil toxicity value for the mixture is estimated to be ≥ 100 mg/kg.
Terrestrial vertebrate	This product is not considered harmful to terrestrial vertebrates. No LC ₅₀ (diet) data for ingredients are available and the classification is based on the LD ₅₀ (oral) – see section 11 – oral toxicity.
Terrestrial invertebrate	The mixture is not considered harmful to terrestrial invertebrates.
Biocidal	Not designed as a biocide.

13. Disposal Considerations

Restrictions	Local council and resource consent conditions may apply, including requirements of trade waste consents.
Disposal method	Disposal of this product must comply with the requirements of the Resource Management Act for which approval should be sought from the Regional Authority. May be buried in approved land disposal facility in accordance with local regulations.
Contaminated packaging	There are no product-specific restrictions however, local council and resource consent conditions may apply, including requirements of trade waste consents.

**14. Transport Information**

Transport according to NZS 5433 (Transport of Hazardous Substances on Land). It is not considered a hazardous substance for transport.

UN number:	NA	Proper shipping name:	NA
Class(es)	NA	Packing group:	NA
Precautions:	NA	Hazchem code:	1T (recommended)

15. Regulatory Information

This product is an approved substance under the Hazardous Substances and New Organisms Act (HSNO). Approval code: HSR002545: Construction Products (Toxic [6.7A]) Group Standard 2006.

Specific Workplace Controls (as per HSNO approval referenced to Controls Matrix)

Note: the controls apply to dust of hardened masonry.

Key workplace requirements are:

SDS	To be available within 10 minutes in workplaces storing any quantity.
Labelling	No removal of labels and/or decanting of product into other containers can occur.
Emergency plan	Required if > 1000kg is stored.
Approved handler	Approved handlers are NOT required if this product is used in the construction industry (exempted requirement under construction group standard).
Tracking	Not required.
Bunding and secondary containment	Required if > 1000kg is stored.
Signage	Required if > 1000kg is stored.
Location Test certificate	Not required.
Flammable zone	Not required.
Fire extinguisher	Not required.

Other Legislation

In New Zealand, the use of this product may come under the Resource Management Act and Regulations, the Health, Safety in Employment Act and Regulations, local Council Rules and Regional Council Plans.

**16. Other Information****Abbreviations**

Approval Code	For Masonry dust: Approval Construction Products (Toxic [6.7A]) Group Standard 2006, Controls, EPA. www.epa.govt.nz
CAS Number	Unique Chemical Abstracts Service Registry Number
Ceiling	Ceiling Exposure Value: The maximum airborne concentration of a biological or chemical agent to which a worker may be exposed at any time.
Controls Matrix	List of default controls linking regulation numbers to Matrix code (e.g. T1, I16).
EC₅₀	Ecotoxic Concentration 50% – concentration in water which is fatal to 50% of a test population (e.g. daphnia, fish species)
EPA	Environmental Protection Authority (formally known as ERMA)
ERMA	Environmental Risk Management Authority (now known as EPA)
HAZCHEM Code	Emergency action code of numbers and letters that provide information to emergency services, especially fire fighters
HSNO	Hazardous Substances and New Organisms (Act and Regulations)
IARC	International Agency for Research on Cancer
LEL	Lower Explosive Limit
LD₅₀	Lethal Dose 50% – dose which is fatal to 50% of a test population (usually rats).
LC₅₀	Lethal Concentration 50% – concentration in air which is fatal to 50% of a test population (usually rats)
SDS	Material Safety Data Sheet (or Safety Data Sheet)
OSH	The Occupational Safety and Health Service of the Department of Labour (NZ)
STEL	Short Term Exposure Limit - The maximum airborne concentration of a chemical or biological agent to which a worker may be exposed in any 15 minute period, provided the TWA is not exceeded
TWA	Time Weighted Average – generally referred to WES averaged over typical work day (usually 8 hours)
UEL	Upper Explosive Limit
UN Number	United Nations Number
WES	Workplace Exposure Standard - The airborne concentration of a biological or chemical agent to which a worker may be exposed.

References

Data	Unless otherwise stated comes from the EPA HSNO chemical classification information database (CCID) http://www.epa.govt.nz/hs/compliance/chemicals.html , for specific chemicals.
EPA Transfer Gazettes	Classifications and controls assigned for specific ingredients (consolidated gazette, 2004)
Controls Matrix	Part of the EPA New Zealand User Guide to the HSNO Control Regulations
WES 2011	The NZ Workplace Exposure Standards Effective from 2011, published by OSH and available on their web site – www.osh.dol.govt.nz .
Other References:	Ingredients SDS's.

Review

Date	Reason for Review
April 2012	NA - new SDS

Disclaimer

This SDS was prepared by Datachem LTD and is based on our current state of knowledge, including information obtained from suppliers. The SDS is given in good faith and constitutes a guideline (not a guarantee of safety). The level of risk each substance poses is relevant to its properties (as summarised in the SDS) AND HOW THE SUBSTANCE IS USED. While guidelines are given for personal protective equipment, such precautions must be relevant to the use. The likely HSNO classifications, are based on our experience, EPA Guidelines and international classifications. A compliance record is available on request. This SDS is copyright Datachem and must not be copied, edited or used for other than intended purpose. To contact the SDS author, email info@datachem.co.nz or phone: **(09) 940 30 80**.

