## Polysafe Modena

granite decoration, ideal where underfoot performance and good aesthetics are key considerations. Used in areas which are normally dry but where are risks of water spillage, Modena features carborundum-free safety particles to ensure full HSE serveries and changing rooms. For continually wet areas such as showers, please refer to our Polysafe Hydro, Hydro Evolve or Ultima ranges.



|     | Gauge   | EN 428/ISO 24346  | 2.0mm   |
|-----|---|---|---|
| - 1 | Wear Layer  | EN 429/ISO 24340  | 0.70mm  |
| Q – | Roll Size   | EN 426/ISO 24341  | 2m x 20m = 40m <sup>2</sup>   |
| 5 - | Total Weight  | EN 430/ISO 23997  | 2780g/m <sup>2</sup>  |
|     | General Performance   | EN 13845<br>ASTM F1303  | Conforms<br>Conforms  |
|     | Use Area  | EN 685/ISO 10874  |   |
| 9 - | Resistance to Chemicals   | EN 423  | Good chemical resistance  |
|     | Reaction to Fire  | EN 13501-1<br>ASTM E648   | Class Bfl-S1<br>Class 1   |
| Ð   | Abrasion Resistance   | EN 13845<br>EN 649  | 50,000 cycles<br>Group T  |
|     | Enhanced Slip Resistance  | EN 13845<br>AS 4586<br>DIN 51130<br>RRL Pendulum Test<br>Surface Roughness<br>The wet slip resistance across all Polysafe product<br>of the product, with strict adherence to HSE Gui<br>resistance, consult Polyflor.                      | ESf<br>R10<br>R10<br>≥36 (wet test - 4S Rubber/Slider 96)<br>Rz ≥20µm<br>ucts is sustainable throughout the guaranteed life<br>idelines. For further clarification regarding slip |
|     | Electrical Behaviour (body voltage)   | EN 1815   | ≤2kV Classified as 'antistatic'   |
| 3   | VOC Emissions   | Indoor Air Comfort GOLD<br>AgBB VOC test<br>Floorscore  | Eurofins certified product<br>Very low emissions<br>Certified   |
|     | Responsible Sourcing  | BES 6001  | Very Good   |
|     | Agrément Assurance - Polysafe Modena PUR has been independently assessed by the British Board of Agrément and product performance is assured for least 10 years in recommended use areas. With proper maintenance, the appearance, colour and slip resistance will be retained during this period.  |   |   |
|     | Environmentally Preferable Flooring - Polysafe Modena PUR achieves BRE Global A+ rating (ENP 415) in the Green Guide to Specification in use areas such education and healthcare and is GreenTag LCA Rate certified with GreenRate level A - Silver Plus, Generic EN 15804 Environmental Product Declaration (EPI available on request. It is 100% recyclable and contains 10% recycled material. Recyclable via the Recofloor scheme. Visit www.polyflor.com/sustainability. |   |   |
|     | Polysafe PUR - Polysafe Modena PUR features a high quality, cross-linked polyurethane reinforcement, UV cured to provide superior cleaning benefits, life cycle maintenance savings and optimum appearance retention. As with all Polysafe products, Polysafe Modena PUR should not have a polish applied.  |   |   |
|     | Hygiene - All Polyflor commercial sheet vinyl ranges provide a continuous, impervious and hygienic flooring solution which can be confidently accordance with recommended maintenance procedures and approved maintenance products. The implementation of an effective cleaning re most important defence against infection.  |   |   |
| )   | Polysafe safety flooring ranges have good resistance<br>and are suitable for steam cleaning on a periodic bas<br>adhesives, maintenance, applications, chemical resist<br>email tech@polyflor.com.<br>As with all Polysafe products, Polysafe Modena PUR :<br>The data presented is correct at the time of printing.<br>Decoration and shade may vary slightly from the sa  | is. Chemical resistance charts available on request.<br>ance and product warranty, consult <b>Polyflor Custor</b><br>should not have a polish applied. For best results, fl<br>For latest information, please visit our website <b>poly</b> | For information regarding handling and installation,<br>ner Technical Services on +44 (0)161 767 1912, or<br>ooring must be reverse laid.   |



FLOORING

James Halitend

